

SR POWER

SR186-3-P4i1

Powered By:



Diesel Power



DIESEL GENERATOR SET

Generator Set Output Rating

Voltage (V)	Hz	Phase	PF	Max. Current (A)	Prime (kVA/kW)	Standby (kVA/kW)
220/127	60	3	0.8	610	211/168	232/186

Canopy Model	Dimensions (L x W x H mm)	Weight (Kg)	Fuel - Hours of Run-time
TC3350	3350 x 1120 x 1850	2310	6-8h
Open Model	Dimensions (L x W x H mm)	Weight (Kg)	Fuel - Hours of Run-time
SR186-3-P4i1	2530 x 950 x 1800	2007	6-8h

Standard Configuration	Test Condition and Standards
<ul style="list-style-type: none"> Engine (Perkins) Channel Steel Base 24V Charging Alternator GE Circuit Breaker 24V Starter Battery and Connecting Cable Flexible Pipe, Exhaust Elbow, Industrial Silencer, etc. 	<ul style="list-style-type: none"> Ambient Temperature: $\leq 27^{\circ}\text{C}$ Relative Humidity: $\leq 60\%$, Altitude: $\leq 1000\text{m}$ Engine: ISO3046, DIN6271, BS5514 Alternator: VDE0530, BS5000, NEMA MG1-32, IEC34 Generator: ISO8528, GB2820 Generator O&M Manuals
<ul style="list-style-type: none"> Alternator (Stamford) 50°C Radiator Air Filter, Diesel Fuel Filter, Lube Oil Filter Control Panel (DSE7320) 	

Engine Technical Data			
Model:	1106D-E70TAG4	Max. Power (kW):	209.4
Induction System:	Turbo-charged	Displacement (L):	7.01
Cylinder Arrangement:	In Line, Four Cycle	Bore (mm) × Stroke (mm):	105 x 135
Number of Cylinders:	6	Compression Ratio:	16.8:1
Governor Type:	Electronic CRIN2	Speed (RPM):	1800

Air System		
Combustion Air Flow (M ³ /min):	Prime: 15.2	Standby: 15.4

Exhaust System			
Combustion Gas Flow (M ³ /min):	33.82/34.27	Max. Back Pressure (kPa):	15
Exhaust Gas Temperature:	509°C	Exhaust Outlet Size (mm):	116

Lubrication System			
Total Oil Capacity (L):	17.5	Oil Consumption 100% Load (L/h):	0.0483/0.0522
Normal Oil Temperature (°C):	125	Recommended Oil:	API CH-4 15W/40

Cooling System			
Cooling System Capacity (L):	21	Max. Coolant Temperature (°C):	110
Thermostat Operation Range (°C):	82-95	Radiator Fan Drive Type:	Shaft Drive
		Radiator Power (kW):	10

Fuel System

Fuel Injection Pump:	CB28	Recommended Fuel:	BS2869:1998 Class A2 Diesel
Fuel Consumption 100% Load (L/h):	48.3	Fuel Consumption 110% Load (L/h):	52.2

Engine Electrical System

Voltage:	12Vdc
----------	-------

Alternator Physical Data

Model:	UCI274G	Rated Power (kVA):	234
Phase:	3	Number of Bearings:	1
Excitation System:	Self-Excited and Brushless	AVR:	AS440
Connection:	3P 4W, Parallel Star	Insulation Class/Temp Rise:	H/H
Power Factor:	0.8	Wave form NEAM=TIF:	<50
Ingress Protection Rating:	IP23	Wave form IEC=THF:	<2%
Winding Pitch:	2/3	Voltage Regulation:	±1%
Cooling Air (M ³ /s):	0.514	Efficiency:	92.1%

Warranty

The standard warranty period: One year after ex-works from factory or 1500 operation hours whichever come occurs first.

- **The model name and output rating figures are base on 400V and may have a 2% deviation**
- **Specifications subject to change without prior notice**



SR POWER

10151 Business Drive, Miramar, Florida 33025 - United States