

SR POWER

SR345-3-P4i1

Powered By:



Diesel Power



DIESEL GENERATOR SET

Generator Set Output Rating

Voltage (V)	Hz	Phase	PF	Max. Current (A)	Prime (kVA/kW)	Standby (kVA/kW)
220/127	60	3	0.8	1132	393/315	431/345

Canopy Model	Dimensions (L x W x H mm)	Weight (Kg)	Fuel - Hours of Run-time
TC4320-2	4320 x 1440 x 2400	4400	6-8h
Open Model	Dimensions (L x W x H mm)	Weight (Kg)	Fuel - Hours of Run-time
SR345-3-P4i1	3190 x 1120 x 2085	3251	6-8h

Standard Configuration	Test Condition and Standards
<ul style="list-style-type: none"> Engine (Perkins) Channel Steel Base 24V Charging Alternator GE Circuit Breaker 24V Starter Battery and Connecting Cable Flexible Pipe, Exhaust Elbow, Industrial Silencer, etc. 	<ul style="list-style-type: none"> Ambient Temperature: $\leq 27^{\circ}\text{C}$ Relative Humidity: $\leq 60\%$, Altitude: $\leq 1000\text{m}$ Engine: ISO3046, DIN6271, BS5514 Alternator: VDE0530, BS5000, NEMA MG1-32, IEC34 Generator: ISO8528, GB2820 Generator O&M Manuals
<ul style="list-style-type: none"> Alternator (Stamford) 50°C Radiator Air Filter, Diesel Fuel Filter, Lube Oil Filter Control Panel (DSE7320) 	

Engine Technical Data

Model:	2206D-E13TAG2	Max. Power (kW):	392.5
Induction System:	Turbo-charged	Displacement (L):	12.5
Cylinder Arrangement:	In Line, Four Cycle	Bore (mm) × Stroke (mm):	130 x 157
Number of Cylinders:	6	Compression Ratio:	16.3:1
Governor Type:	Electronic	Speed (RPM):	1800

Air System

Combustion Air Flow (M ³ /min):	Prime: 25.1	Standby: 26.6
--------------------------------------------	-------------	---------------

Exhaust System

Combustion Gas Flow (M ³ /min):	71.5/76.6	Max. Back Pressure (kPa):	10
Exhaust Gas Temperature:	680°C	Exhaust Outlet Size (mm):	123

Lubrication System

Total Oil Capacity (L):	40	Oil Consumption 100% Load (L/h):	0.13/0.14
Normal Oil Temperature (°C):	113	Recommended Oil:	API CH-4 15W/40

Cooling System

Cooling System Capacity (L):	51.4	Max. Coolant Temperature (°C):	104
Thermostat Operation Range (°C):	87-98	Radiator Fan Drive Type:	Shaft Drive
Radiator Cooling Air Flow (M ³ /min):	788	Radiator Power (kW):	14.0

Fuel System

Fuel Injection Pump:	MEUI	Recommended Fuel:	BS2869:1998 Class A2 Diesel
Fuel Consumption 100% Load (L/h):	87	Fuel Consumption 110% Load (L/h):	94

Engine Electrical System

Voltage:	24Vdc
----------	-------

Alternator Physical Data

Model:	HCI444ES	Rated Power (kVA):	345
Phase:	3	Number of Bearings:	1
Excitation System:	Self-Excited and Brushless	AVR:	AS440
Connection:	3P 4W, Parallel Star	Insulation Class/Temp Rise:	H/H
Power Factor:	0.8	Wave form NEAM=TIF:	<50
Ingress Protection Rating:	IP23	Wave form IEC=THF:	<2%
Winding Pitch:	2/3	Voltage Regulation:	±1%
Cooling Air (M ³ /s):	0.8	Efficiency:	93.7%

Warranty

The standard warranty period: One year after ex-works from factory or 1500 operation hours whichever come occurs first.

- **The model name and output rating figures are base on 400V and may have a 2% deviation**
- **Specifications subject to change without prior notice**



SR POWER

10151 Business Drive, Miramar, Florida 33025 - United States